KRETUS GROUP®

Safety Data Sheet



SECTION 1: IDENTIFICATION

Product Name: KRETUS® Anti-Slip Bead 50 or 100

Recommended Use: For residential and industrial use

Manufacturer: Kretus Group®, 1055 W. Struck Ave., Orange, CA 92867

Telephone: (714) 694-2061

24 Hour Emergency Telephone Number: (800) 255-3924 (CHEMTEL)

Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

Comments: To the best of our knowledge, this Safety Data Sheet conforms to the requirements of US OSHA 29 CFR1910.1200.

SECTION 2: HAZARD IDENTIFICATION

Eye Irritation: Category 1 Aspiration Hazard: Category 1

Warning

Causes serious eye irritation. May cause respiratory irritation.



Keep container tightly closed. Wash hands thoroughly after handling. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection.

Classification: Organic Powder

OSHA 29CFR 1910.1200: Combustible dust

REGULATION (EC) No 1272/2008: Not a hazardous substance or mixture

OSHA 29CFR1910.1200

WARNING - May form combustible dust concentrations in the air

REGULATION (EC) No 1272/2008: Not a hazardous substance or mixture. These products are micronized powders. Static charges on the powders may ignite flammable atmospheres. High levels of product dust in the atmosphere may present a dust explosion hazard.

Other useful guides to handling organic powders include: NFPA 77 Recommended Practice on Static Electricity NFPA 654 Standard for the Prevention of Fire and Dust Explosions from the Manufacturing,

SDS_Anti-SlipBead50-100.docx 6/14/19 (Page 1 of 6)

Processing, and Handling of Combustible Particulate Solids

NFPA 499 Recommended Practice for the Classification of Combustible Dusts and of Hazardous

(Classified) Locations for Electrical Installations in Chemical Process Areas

OSHA 3371-08 Hazard Communication Guidance for Combustible Dusts

DUST HAZARD - Notification given pursuant to Table 1.5.2 of the 3rd Revision of GHS (2009).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Chemical Name	CAS No.	Concentration (% by Weight)
Polypropylene homopolymer	9003-07-0	100

SECTION 4: FIRST-AID MEASURES

Contact with Eyes

Flush with copious amounts of water for at least 15 minutes. IMMEDIATE MEDICAL ATTENTION IS NECESSARY.

Contact with Skin

If burned by hot wax, quench immediately with cold tap water. Dry burn area and loosely cover to

protect against infection. Do not apply ointment or salves. IMMEDIATE MEDICAL ATTENTION IS NECESSARY.

Inhalation

Treat as a nuisance dust. Remove victim to fresh air and provide oxygen if breathing is difficult. Immediate medical attention not normally required. No delayed effects expected.

Ingestion

If large quantities are ingested – IMMEDIATE MEDICAL ATTENTION IS NECESSARY. Do not give anything to an unconscious person.

Acute

None known.

Delayed and Chronic Effects

None known. Not listed by NTP, IARC, or OSHA as a carcinogen.

SECTION 5: FIRE-FIGHTING MEASURES

OSHA FLAMMABILITY CLASS: Combustible solid

Suitable Extinguishing Media

Carbon Dioxide (CO₂), dry chemical or fine water spray. Avoid water stream on molten burning material as it may scatter and spread the fire.

Special Protective Equipment for Fire-Fighting

Wear self-contained breathing apparatus and protective clothing approved by NIOSH. Watch footing on floors and stairs because of possible melting and spreading of material. Use spray to keep containers cool.

Special Risks: Unusual Fire and Explosion Hazards

Flash point >530°F (277°C).

Melts in proximity to fires, causing slippery floors and stairs. When powder is suspended in air, these products could be FLAMMABLE/EXPLOSIVE.

SDS_Anti-SlipBead50-100.docx 6/14/19 (Page 2 of 6) In these circumstances, keep away from heat, sparks and open flames. Static charges on powders or powders in liquids may ignite flammable atmospheres. See Section 7 "HANDLING AND STORAGE" for suggestions on how to use these products under such conditions. Also refer to NFPA Bulletin 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", for safe handling procedures.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Wear rubber boots with slip-resistant soles, and NIOSH-approved dust respirator where dust occurs. See section 8.

Environmental Precautions:

Sinks in water. No known hazard to aquatic life.

Methods and Materials for Containment and Clean-up:

Collect with HEPA Filter Dust Collector. Ensure adequate ventilation. Do not walk through spilled material.

Avoid Static charge at high levels.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe-Handling

Avoid contact with skin, eyes, and clothing. Wash hands before eating or drinking. Avoid accumulation of dust. Use only in well-ventilated areas.

Conditions for Safe Storage

Store in the original container in a cool, dry, well-ventilated area. Keep containers tightly sealed.

Storage temperature: Ambient.

Storage life: N/A

Incompatible Materials

Dissolves in hydrofluoric acid.

Extra Information

- Avoid projections and probes that could lead to discharge between the charged polymer and probe.

- Never pour micronized polymers or waxes from a drum or large container directly into hot flammable solvents.

- Add micronized polymers or waxes slowly and in small quantities to hot flammable solvents.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION				
Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Organic Powder	-	LTEL TWA	IDLH: -	
		10-15 mg/m3 (total dust)	TWA: -	
		3-5 mg/m3 (respirable)	TWA: -	

Engineering Controls: Use adequate ventilation during heating processes or if dusty conditions prevail when handling powdered materials. For storage and ordinary handling, general ventilation is adequate.

Respiratory protection: Use a NIOSH-approved dust respirator with powdered wax. During melting or

conveying in molten state, use organic vapor respirator.

Ventilation: Face velocity greater than 60 cfm (adequate to capture wax dust or fumes).

Eye/face protection: Chemical goggles around molten material and in dusty conditions.

Skin protection: Use heat resistant, impervious gloves to avoid repeated/prolonged skin contact with molten material and powder. Other protective garments as necessary.

Other Personal Protective Equipment: As needed to prevent repeated/prolonged contact.

Work/Hygienic Practices: Wash skin thoroughly with soap and warm water after handling and before smoking, eating, or applying makeup. If clothes become contaminated, change to clean clothing. Do not wear contaminated clothing until properly laundered. Further information relating to the safe handling and use of fluorocarbon polymers may be found in DWE (NIOSH), Publication No. 77-193.

Exposure Guidelines: Powdered forms may generate nuisance particulates upon handling.

ACGIH TLV = 10mg/m3. OSHA PEL 5mg/m3.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance	solid, white powder	
Odor Threshold	n/a	
РН	8	
Melting/Freezing Point	330°C	
Initial Boiling Point and Boiling Range	n/a	
Flash Point	>530°F	
Evaporation Rate	n/a	
Vapor Pressure	nil	
Relative Density	0.90 g/cc	
SCAQMD VOC	0 mg/L	

SECTION 10: STABILITY AND REACTIVITY

Reactivity: None under normal conditions.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: None under normal processing.

Condition(s) to Avoid: Extreme heat, sparks and open flame.

Substance(s) to Avoid: Pre-mixing over 24hours prior to application. Strong oxidizing agents and amines.

Hazardous Decomposition Product(s): These products may emit oxides of carbon and nitrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

Treat as nuisance dust.

After inhalation: Inhalation of the dust may cause breathlessness, coughing, tightness of the chest and difficulty in breathing.

After eye contact: Slightly irritating to the eye. Avoid getting product airborne.

After skin contact: Slightly irritating to the skin.

After ingestion: No data.

Irritation: Causes eye irritation. May cause respiratory irritation. May cause transient irritation.

Corrosivity: No data.

Sensitization: No data.

Repeated Dose Toxicity: None known.

Mutagenicity: No data.

Toxicity for Reproduction: No data.

SECTION 12: ECOLOGICAL INFORMATION

SDS_Anti-SlipBead50-100.docx 6/14/19 (Page 4 of 6)

WASTE DISPOSAL METHOD: Assume conformity with applicable disposal regulations. Preferred method of disposal is in closed containers of enough strength to eliminate leakage at approved incineration or chemical landfill waste disposal site in accordance with local regulations. Sewage disposal is discouraged.

Toxicity: No known reports of ecotoxicity to the environment.

Persistence and Degradability: Persistent but inert in aquatic systems.

Bio accumulative Potential: The product will not bioaccumulate up the food chain.

RCRA: Is the unused product a RCRA hazardous waste if discarded? No.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposed material is not a hazardous waste. Disposal should be in accordance with local, state or national legislation. Containers must not be punctured or destroyed by burning, even when empty.

SECTION 14: TRANSPORT INFORMATION

US DOT PROPER SHIPPING NAME: N/A

US DOT ID NUMBER: N/A

US DOT HAZARD CLASS: N/A

US DOT PACKAGING GROUP: N/A

The transportation information listed above is suitable for all modes of transportation. TDG, IMO/IMDG, ICAO/IATA, 49 CFR

SECTION 15: REGULATORY INFORMATION

United States:

TSCA (Toxic Substance Control Act): This product or its components are listed on the TSCA Inventory. This product or its components do not contain any chemicals subject to any rules or orders under TSCA sections 4, 5, 6, 7, or 8(d). SARA 311/312—Hazard Categories: Immediate/Acute Health (irritant): YES

SARA 302—Extremely Hazardous Substances: Not hazardous

SARA 313—Toxic Chemicals: Not toxic

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): Not established

CAA (Clean Air Act 1990): No data

CWA (Clean Water Act): No data

California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) - This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other reproductive harm.

Canada

WHMIS Classification: No data

Canada (DSL/NDSL): No data

Canada Ingredient Disclosure List (CIDL): No data

Chemical Safety Assessment: Glass is regarded by FDA as Generally Recognized As Safe (GRAS) for use in contact with food.

SECTION 16: OTHER INFORMATION

HMIS	HMIS	
Health	1	
Flammability	1	
Reactivity	0	
Personal Protection: Safety goggles, neoprene rubber gloves, N95 respirator		

SDS_Anti-SlipBead50-100.docx 6/14/19 (Page 5 of 6)

Additional Information: The accumulation of airborne dust particles may lead to health and safety risks in some cases. The use of good industrial practices will mitigate this risk.

The health risks from inhalation of dust particles vary; this is due to particle concentration, exposure length, number of exposures and type of particles inhaled. Please read Sections 2,4,6,7 and 8 of the SDS to understand these potential risks. Wear personal protective equipment and follow storage and handling procedures to maintain a safe workplace.

In rare instances, combustible dusts may represent a potential explosion hazard when airborne. This hazard is often associated with organic dust such as foodstuffs and coal but may also occur with mineral products. While the majority of our products would be considered non-combustible, the overall airborne environment should be considered when determining the need for mitigation from

Prepared by Kretus Group

Revision date 3/1/19

Revision Note No information available

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.